Haier Display

HV-926TB Specification

Bezel color options	silver/black/black, silver/grey/grey, red/black/black, black/white/black, silver/purple/purple, beige color, ivory white color
TFT panel	LG.PHILIPS/ Hannstar/CPT
Speaker	with
Dot pitch (mm)	0.294
View angel	H:+80/-80; V:+80/-80
Resolution (maximum/best)	1280x1024@75Hz/1280x1024@60Hz
Max contrast ratio:	600 : 1
Max brightness:	250cd/m
Response time tr/tf:	12ms
Color:	16.7M
Input signal:	Analog
Input DVI:	+USD4
Control manner	OSD
Logo on front	Logo plate or silk screen
Power consumption operating/suspend/off	<45W/<5W/<3W
Power supply	AC100-240V 60/50Hz, 1.5A, 12V DC, 4.2A
Operating temperature	5~40 centi degree
Operating humidity	20% -80%
Storage temperature	-20~45 centi degree
Storage humidity	10% -90%
Certificate	CE, FCC, CB, TCO99, ISO9001
Packing carton size (mm):	490X165X465
Weight (kg)	NW:6.0; GW:8.0
Container load w/o pallet (MOQ)	816pcs/20'; 1680pcs/40' ; 1680pcs/40'HQ
Container load with pallet (MOQ)	648pcs/20'; 1344pcs/40' ; 1680pcs/40'HQ